

UNOCAL 76

PORSF  
11.3.125/101  
07/16/85Product Name: UNOCAL UNAX AW 46  
PRODUCT CODE NO: 04642

ISSUE DATE: 7/16/85

PAGE 1 OF 4

## MANUFACTURER:

UNOCAL REFINING & MARKETING DIVISION  
UNION OIL COMPANY OF CALIFORNIA  
1201 W. 5TH STREET  
LOS ANGELES, CALIFORNIA 90017CONTACT FOR FURTHER INFORMATION:  
MSDS COORDINATOR (213) 977-7589

## Transportation Emergencies:

Call CHEMTREC  
(800) 424-9300 Cont. U.S.  
(202) 483-7616 (Collect)  
from Alaska & Hawaii

## Health Emergencies:

CALL LOS ANGELES POISON  
INFORMATION CENTER (24 hrs.)  
(213) 664-2121

## PRODUCT IDENTIFICATION

PRODUCT NAME: UNOCAL UNAX AW 46 Hydraulic

SYNONYMS: UNION UNAX AW 46

GENERIC NAME: INDUSTRIAL OILS

CHEMICAL FAMILY: PETROLEUM HYDROCARBON

## DOT PROPER

SHIPPING NAME: NOT APPLICABLE

ID NUMBER: NONE

## SECTION I - INGREDIENTS

TLV UNITS AGENCY TYPE

OIL MIST, IF GENERATED

5.00 MG/M3 OSHA

FULL TERM TWA

THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM  
THIS LIST.

## SECTION II - EMERGENCY AND FIRST AID PROCEDURES

\*\*\*EMERGENCY\*\*\*

Have physician call LOS ANGELES POISON  
INFORMATION CENTER (24 hrs.) (213) 664-2121

## EYE CONTACT:

FOR DIRECT CONTACT, FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER. IF IRRITATION OR  
REDNESS DEVELOPS, SEEK MEDICAL ATTENTION.

## SKIN CONTACT:

DO NOT USE GASOLINES, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL  
FROM SKIN AND REMOVE CONTAMINATED CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY  
WASHING WITH SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF  
IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

## INHALATION (BREATHING):

IF IRRITATION OF NOSE OR THROAT DEVELOPS, MOVE AWAY FROM SOURCE OF EXPOSURE AND INTO  
FRESH AIR. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING  
OR IF BREATHING DIFFICULTIES DEVELOP, ARTIFICIAL RESPIRATION OR OXYGEN SHOULD BE  
ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.

## INGESTION (SWALLOWING):

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2 TO 3 CUPS OF MILK OR WATER TO DRINK. SEEK  
MEDICAL ATTENTION. TO PHYSICIAN: EMESIS OR LAVAGE IS NOT RECOMMENDED FOR INGESTIONS  
OF MINUTE QUANTITIES OR TASTES OF MOST HYDROCARBONS. MEDICAL OPINION IS DIVIDED FOR  
LARGER INGESTIONS. EMESIS OR LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM  
PRODUCTS WHICH HAVE A HIGH ORAL TOXICITY. GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL  
TUBE IS RECOMMENDED BY SOME PHYSICIANS TO PREVENT ASPIRATION.

USEPA SF



1265439

SECTION III - POTENTIAL ADVERSE HEALTH EFFECTS

EYE CONTACT:

THIS MATERIAL MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE BURNING, TEARING AND REDNESS.

SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DERMATITIS.

INHALATION (BREATHING):

EXPOSURE TO MISTS, OR PROLONGED OR REPEATED EXPOSURE TO FUMES OR VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY CAUSE IRRITATION OF NOSE AND THROAT.

INGESTION (SWALLOWING):

ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION:

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE LIMITS, A SUITABLE FILTER-TYPE RESPIRATOR SHOULD BE WORN. (SEE SECTION I.)

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES AND SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OIL-BASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH ANY SOURCE OF IGNITION.

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS. EXTENDED EXPOSURE TO HIGH TEMPERATURES MAY CAUSE DECOMPOSITION.

SECTION V - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD MAJOR AMOUNTS OF OXIDES OF CARBON AND MINOR AMOUNTS OF OXIDES OF SULFUR AND NITROGEN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

SECTION VI - SPILL OR LEAK PROCEDURES

\*\*\*HIGHWAY OR RAILWAY SPILLS\*\*\*  
Call CHEMTREC (800) 424-9300 Cont. U.S.  
(Collect) (202) 483-7616 from Alaska & Hawaii

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBANT. CONTACT FIRE AUTHORITIES AND APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES, NOTIFY COAST GUARD NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR OIL-SOAKED CLOTHING OR SHOES.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

| <u>HAZARD RANKING</u>   |                  |              |                       |                    |
|-------------------------|------------------|--------------|-----------------------|--------------------|
| NFPA<br>HAZARD<br>CLASS | HEALTH HAZARD: 0 | 0 = LEAST    | DOT FLAMMABILITY      | <u>FLASH POINT</u> |
|                         | FLAMMABILITY: 1  | 1 = SLIGHT   | <u>CLASSIFICATION</u> |                    |
|                         | REACTIVITY: 0    | 2 = MODERATE |                       |                    |
|                         | OTHER: 0         | 3 = HIGH     | NOT REGULATED         | 410, COC F         |
|                         |                  | 4 = EXTREME  |                       | 210 C              |

EXTINGUISHING MEDIA:

EXTINGUISH WITH DRY CHEMICAL, CO2, WATER SPRAY, FOAM, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY.

FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK.

SECTION IX - PHYSICAL DATA

|                              |                         |                         |                   |
|------------------------------|-------------------------|-------------------------|-------------------|
| <u>APPROX. BOILING RANGE</u> | <u>VAPOR DENSITY</u>    | <u>EVAPORATION RATE</u> | <u>% VOLATILE</u> |
| ABOVE 600 F<br>(316) C       | HEAVIER THAN AIR        | SLOWER THAN ETHER       | NEGLIGIBLE        |
| <u>% SOLUBILITY IN WATER</u> | <u>SPECIFIC GRAVITY</u> | <u>APPEARANCE</u>       | <u>ODOR</u>       |
| NEGLIGIBLE                   | 0.88 - 0.89             | CLEAR, YELLOW           | CHARACTERISTIC    |

SECTION XI - DOCUMENTARY INFORMATION

ISSUE DATE: 7/16/85    PREV. DATE: 7/ 5/84    PRODUCT CODE NO. D4642

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.